

Company name: Created by: Phone:

**Date:** 6/19/2019

# Count | Description

CRN 10-12 A-FGJ-A-E-HQQE



Product No.: 96522950

Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation.

The pump has the following characteristics:

- Impellers, intermediate chambers and outer sleeve are made of
  - Pump head cover and base are made of
- The shaft seal has assembly length according to EN 12756.
- Power transmission is via cast iron split coupling.

flanges/couplings.

The motor is a 1-phase AC motor.

## Controls:

Frequency converter: NONE

Liquid:

Pumped liquid: Water
Liquid temperature range: -4 .. 248 °F
Selected liquid temperature: 68 °F
Density: 62.29 lb/ft³

Technical:

Rated pump speed: 3500 rpm
Rated flow: 53.3 US gpm
Rated head: 462 ft
Pump orientation: Vertical
Shaft seal arrangement: Single
Code for shaft seal: HQQE
Approvals on nameplate: CURUS

Curve tolerance: ISO9906:2012 3B

Materials:

Base: Stainless steel

EN 1.4408 AISI 316 Stainless steel

Impeller: Stainless steel

EN 1.4401 AISI 316

Bearing: SIC

Installation:

Maximum ambient temperature: 104 °F Maximum operating pressure: 362.59 psi



Company name: Created by: Phone:

**Date:** 6/19/2019

## Count | Description

Max pressure at stated temperature: 363 psi / 250 °F

363 psi / -4 °F

Type of connection: DIN / ANSI / JIS

Size of inlet connection: DN 50
Size of suction port: 2 inch
Size of outlet connection: DN 50
Size of outlet port: 2 inch
Pressure rating for pipe connection: PN 25
Flange rating inlet: 300 lb
Flange size for motor: 213TC

#### Electrical data:

Motor standard: **NEMA** Motor type: Baldor Rated power - P2: 10 HP Power (P2) required by pump: 10 HP Main frequency: 60 Hz Rated voltage: 1 x 230 V Service factor: 1.15 Rated current: 40 A Rated speed: 3525 rpm

Number of poles: 2 Insulation class (IEC 85): F

Motor Number: 85700022

### Others:

Net weight: 262 lb
Gross weight: 377 lb
Shipping volume: 21.9 ft³
Country of origin: US

Custom tariff no.: 8413.70.2040