



Features _

- Unique rimless bowl design
- Uses 20% less water than conventional toilets
- 1.28 gpf / 4.86 lpf low water consumption
- Round front bowl
- 3" flush valve
- Pilot operated fill valve
- 12" rough-in
- 2" glazed trapway
- Chrome trip lever
- The Mansfield® limited lifetime warranty
- Available in White







Components _____

Model #	Description	Codes/Standards
4810-3816	Round front, two-piece toilet. Less toilet seat and supply.	
4810	Round front toilet bowl only. Less toilet seat.	
3816	Tank and cover only, with left hand, front-mount, chrome trip lever. Less supply.	HIGH EFFICIENCY TOLLET HIGH EFFICIENCY TOLLET LENGTH LENGTH
3816RH	Same as above, with right hand trip lever.	
SB100	Round, toilet seat. Specify color.	





Specifications


Model #	Description	Codes/Standards
4810-3816	Round front (1.28 gpf/4.86 lpf) two-piece toilet	HIGH EFFICIENCY TOLET HIGH EFFICIENCY TOLET GENERAL GE

Specification	Description	Specification	Description
Material	Vitreous china	Trap Diameter	2"
Water Pressure Range	20 to 80 PSI	Trap Seal	2-1/4"
Flush System	Gravity fed flushing technology	Rough-in	12"
Water Usage	1.28 gpf / 4.86 lpf	Shipping Weight	69.8 lbs. (31.7 kg)
Water Surface Area	6-1/2" X 9-1/4"	Warranty	Vitreous China - Limited Lifetime
MaP Rating	800 grams		Tank Trim - Limited One Year

Technical Information.







See our complete line of acrylic and vitreous china bathroom fixtures, plastic tank trim and plumbing products.

These dimensions are nominal and subject to change without notice.

Fixture performance and specifications meet or exceed ASME A112.19.2-2008/CSA B45.1-08 standards, and other state and local codes.