

roject:
xture Type:
ocation:
ontact:

# One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED

# **Description:**

6" downlight wall cylinders are ideal for a wide variety of interior and exterior applications including residential and commercial. The aluminum Cylinders offers a contemporary design with its sleek cylindrical form and elegant fade and chip resistant Metallic Gray finish, perfect for today's inspired exteriors. With over 1,500 lumens the LED Cylinders unite performance, energy savings and safety benefits.

## **Specifications:**

- · Metallic Gray (-82) (powder coat paint)
- · Die cast and extruded aluminum Construction
- · Metallic Gray finish.
- · Interior finish matches exterior finish.
- · Die-cast aluminum construction with durable powder coated finish
- · 1,355 lumens 46 lumens/watt
- · 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · Meets California Title 24 high efficacy requirements for outdoor use only

#### Performance:

Number of Modules	1
Input Power	29.3w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	933/31.8 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 ℃
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	Meets California Title 24 high efficacy requirements
	for outdoor use only

# P5641-82/30K

#### Images:



#### **Dimensions:**

Width: 6" Depth: 8-7/8" Height: 12" H/CTR: 4-1/2"



# One-Light Outdoor



P5641-82/30K

## **Dimming Notes:**

P5641 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Diva DVELV-300P

Lutron Nova NTELV-300

Lutron Vierti VTELV-600

Lutron MAELV-600

Lutron SPELV-600

Leviton AWRMG-EAW

Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.