

TLG10305U

GB Single Lavatory Faucet - Vessel

FEATURES

- WaterSense[®] certified low-flow 1.2 gpm (4.5 lpm) faucet
- Smooth handle control COMFORT GLIDE[®] technology
- Diamond-like Carbon (DLC) coated ceramic cartridge for ultimate durability
- Brass construction
- Lever handles
- Metal pop-up drain assembly included

COLORS/FINISHES

- #CP Polished Chrome
- #PN Polished Nickel
- #BN Brushed Nickel

Made to Order

- #PFG Polished French Gold
- #PBR Polished Bronze
- #PBL Polished Black
- #PRG Polished Rose Gold
- #MBL Matte Black
- #BRG Brushed Rose Gold

OPTIONAL ACCESSORIES

- THP3158#CP 4" Cover Plate
- THP3159#CP 8" Cover Plate

PRODUCT SPECIFICATION

Product shall have a maximum flow rate of 1.2 gpm (4.5 lpm). Product shall have a brass construction. Product shall have lever handles. Product shall have a ceramic disk valve cartridges. Product shall include metal pop-up drain assembly. Product shall be TOTO Model TLG10305U#____.



CODES/STANDARDS


- Meets or exceeds ASME A112.18.1/CSA B125.1, NSF 61/NSF 372
- Certifications: IAPMO(cUPC), EPA WaterSense,
- State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada,
- and others
- California Green Building Code, City of Los
- Angeles Water Efficiency Ordinance
- Complies with federal and state requirements as lead-free (weighted average of 0.25% lead or less)
- ADA compliant
- Complies with CA Prop 65 warning requirements




GB Single Lavatory Faucet - Vessel

SPECIFICATIONS

Material	Brass	[
Maximum Flow Rate	1.2 gpm (4.5 lpm)		1.2	, [
Warranty	Lifetime Limited Warranty (Residential Use) One Year (Commercial Use)		1 7 ^{0.8}	
			8.0 gpm)	



DIMENSIONS



NOTE: The above dimensional unit is inch. The dimension in () is reference mm.